## CBCO-G-2 Gas Convection Oven

Model: CBCO-G-2 **DESCRIPTION: GAS CONVECTION OVEN TOTAL BTU/HR: 54,000** PACKING SIZE (IN): \*46"X42"X42"

> N/W (LB): 408 G/W (LB): 606

## FEATURES

 STAINLESS STEEL FRONT, GALVANIZED SIDES W/ HD SUPPORT

- DIRECT FIRED GAS BURNER(3, 18,000 BTU/HR EACH)
  - TEMPERATURE ADJUSTS FROM 167°F TO 563°F
  - . PORCELAINIZED INTERIOR FOR EASY CLEANING
    - DUAL PANE THERMAL GLASS WINDOWS
      - 60-MINUTE ELECTRIC TIMER W/ BELL
  - 1/2 HP FAN MOTOR WITH DUAL-SPEED CONTROL
    - REMOVABLE 13-POSITION RACK GUIDES
    - 4 HEAVY DUTY CHROME PLATED RACKS
      - Cool down function
      - INTERIOR CHAMBER LIGHT
- Double stacking options to optimize kitchen space
  - AUTOMATIC IGNITION SYSTEM FOR GAS SAFETY
- MICRO SWITCH FOR COMPLETE SHUT OFF ONCE DOOR IS OPENED
  - 3/4" NPT REAR GAS CONNECTION

STACKING KIT IS TO BE ORDERED ADDITIONALLY

ONE YEAR LIMITED PARTS AND LABOR WARRANTY

Castors included

. STACKING KIT AVAILABLE FOR PURCHASE





## \*Spec is based on single deck. Ovens are shipped in single deck package.

## Installation Instructions

- 1. A GAS PRESSURE REGULATOR SUPPLIED WITH THE UNIT MUST BE INSTALLED. NATURAL GAS 4.0" (102 MM) W.C. PROPANE GAS 10.0" (254 MM) W.C.
- 2. An adequate ventilation system is required for commercial cooking equipment.
- 3. THESE UNITS ARE MANUFACTURED FOR INSTALLATION IN ACCORDANCE WITH NATIONAL FUEL GAS CODE, ANSI- Z223.1/NFPA #54 (LATEST EDITION).
- 4. THIS APPLIANCE IS INTENDED FOR COMMERCIAL INSTALLATION ONLY AND IS NOT INTENDED FOR HOME USE.
- 5. EQUIPMENT CLEARANCE REQUIREMENT:

NON-COMBUSTIBLES COMBUSTIBLES SIDES 0" SIDES 4" BACK 0"

BACK 4"



Intertek

6. ALL THE INSTALLATION MUST BE PERFORMED BY QUALIFIED TECHNICIANS.

