CBR-4 Open Burner Gas Restaurant Range w/ Oven

Model: CBR-4

DESCRIPTION: GAS RANGE W/ SINGLE OVEN

Oven Dimensions: 20.4"x25.8"x13.9"

TOTAL BTU/HR: 151,000

PACKING SIZE (IN): 28.3"×40"×44"

N/W (LB): 291

G/W (LB): 357

FEATURES

- STAINLESS STEEL FRONT/BACK RISER W/ GALVANIZED SIDES
 - Cast Iron open burner (30,000 btu/hr each)
 - THERMOSTATICALLY CONTROLLED OVEN (250°F 550°F)
 - WELDED FRAME STRUCTURE FOR SUPERIOR STABILITY
 - STANDBY S/S PILOT FOR EASY START
 - 4 CASTERS FOR EASY MOVING
 - 12"x12"(30x30cm) cast iron grate
 - ANTI-CLOGGING PILOT COVER
- . PULL-OUT CRUMB TRAY W/ ANGLED HANDLE IN THE FRONT
 - U SHAPE OVEN BURNER (31,000 BTU/HR)
 - . THERMAL COUPLING SAFETY VALVE FOR OVEN
 - INSULATED STAINLESS STEEL OVEN DOOR
 - OVEN WITH STAINLESS STEEL HANDLE
 - KICK PLATE AT THE BOTTOM FOR EASY ACCESS
 - 3/4" NPT REAR GAS CONNECTION
 - 2 OVEN RACKS INCLUDED
 - · GAS CONVERSION KITS INCLUDED
 - ONE YEAR LIMITED PARTS AND LABOR WARRANTY



- 1. A GAS PRESSURE REGULATOR SUPPLIED WITH THE UNIT MUST BE INSTALLED. NATURAL GAS 4.0" (102 MM) W.C. PROPANE GAS 10.0" (254 MM) W.C.
- 2. An adequate ventilation system is required for commercial cooking equipment.
- 3. THESE UNITS ARE MANUFACTURED FOR INSTALLATION IN ACCORDANCE WITH NATIONAL FUEL GAS CODE, ANSI- Z223.1/NFPA #54 (LATEST EDITION).
- 4. THIS APPLIANCE IS INTENDED FOR COMMERCIAL INSTALLATION ONLY AND IS NOT INTENDED FOR HOME USE.
- 5. EQUIPMENT CLEARANCE REQUIREMENT:

BACK 0"

NON-COMBUSTIBLES COMBUSTIBLES SIDES 0" SIDES 4"

Васк 4"





Intertek

- 6. ALL THE INSTALLATION MUST BE PERFORMED BY QUALIFIED TECHNICIANS.
- 7. FOR GAS CONVERSION, PLEASE REFER TO CONVERSION INSTRUCTIONS IN THE INSTRUCTION MANUAL BOOK.





