

CBTG-48 48" Wide Gas Griddle w/ Thermostat

MODEL: CBTG-48

DESCRIPTION: 48" WIDE GAS GRIDDLE W/ THERMOSTAT

PLATE SIZE: 48"x19"

TOTAL BTU/HR: 120,000

PACKING SIZE (IN): 50"x30"x20"

N/W (LB): 298

G/W (LB): 375

FEATURES

- STAINLESS STEEL FRONT W/ GALVANIZED SIDES
- STEEL U-SHAPE BURNER (30,000 BTU/HR EACH)
 - CONTROLLED EVERY 12"
 - 5/8" THICK POLISHED GRIDDLE PLATE
- STANDBY S/S PILOT FOR EASY START
 - ADJUSTABLE HEAVY DUTY LEGS
- GREASE TROUGH CHANNEL IN THE FRONT
- STAINLESS STEEL OIL COLLECTOR IN THE BOTTOM
- STAINLESS STEEL SPLASH GUARD ON 3 SIDES
 - DURABLE BRASS CONTROL VALVE
- EASY ACCESS TO PILOT VALVE, W/ ADJUSTMENT SCREW
 - EASY GAS CONVERSION IN FIELD
 - 3/4" NPT REAR GAS CONNECTION
 - SHIPPED WITH GAS REGULATOR
 - GAS CONVERSION KITS INCLUDED
- ONE YEAR LIMITED PARTS AND LABOR WARRANTY

IMAGE
COMING
SOON

OTHER MODELS AVAILABLE



Installation Instructions

1. A GAS PRESSURE REGULATOR SUPPLIED WITH THE UNIT MUST BE INSTALLED. NATURAL GAS 4.0" (102 MM) W.C. PROPANE GAS 10.0" (254 MM) W.C.
2. AN ADEQUATE VENTILATION SYSTEM IS REQUIRED FOR COMMERCIAL COOKING EQUIPMENT.
3. THESE UNITS ARE MANUFACTURED FOR INSTALLATION IN ACCORDANCE WITH NATIONAL FUEL GAS CODE, ANSI- Z223.1/NFPA #54 (LATEST EDITION).
4. THIS APPLIANCE IS INTENDED FOR COMMERCIAL INSTALLATION ONLY AND IS NOT INTENDED FOR HOME USE.
5. EQUIPMENT CLEARANCE REQUIREMENT:

NON-COMBUSTIBLES	COMBUSTIBLES
SIDES 0"	SIDES 4"
BACK 0"	BACK 4"
6. ALL THE INSTALLATION MUST BE PERFORMED BY QUALIFIED TECHNICIANS.
7. FOR GAS CONVERSION, PLEASE REFER TO CONVERSION INSTRUCTIONS IN THE INSTRUCTION MANUAL BOOK.

